

■ CQS series

CQS24 series and CQS48015-50 will be released by August 2007.



Single output Quarter-brick

24V Input	Model	CQS24033-40	CQS24050-28	CQS24120-12
	DC output	3.3V 40A	5V 28A	12V 12A
	Output power	132W	140W	144W
	Input Voltage range	DC24V(18-36V)		

48V Input	Model	CQS48015-50	CQS48018-50	CQS48025-45	CQS48033-45	CQS48050-28	CQS48120-14
	DC output	1.5V 50A	1.8V 50A	2.5V 45A	3.3V 45A	5V 28A	12V 14A
	Output power	75W	90W	112.5W	148.5W	140W	168W
	Input Voltage range	DC48V(36-76V)					

GENERAL SPECIFICATIONS

ENVIRONMENT	Operating temperature	-40°C to +85°C(with derating)
	Cooling method	Convection/Forced air
SAFETY	Agency approvals	UL60950-1,C-UL(CSA60950-1),EN60950-1
OTHERS	Size	57.9 _(W) ×8.5 _(H) ×36.8 _(D) mm
	Weight	40g max

- Industrial standard Quarter-brick with pin-compatible ■ High efficiency, High density design
- Protection circuit for over current, over voltage, low voltage and thermal ■ Remote ON/OFF and adjustable output voltage
- Remote sensing ■ No use of aluminum and tantalum electrolytic capacitors for life time ■ 5-year warranty